

Technical Specifications

VIP-580A IP Vandal-Resistant FlexHorn™

- Paging, emergency alerts and tones
- Steel mesh security baffle prevents objects from penetrating the speaker
- Power over Ethernet (PoE) 802.3af compatible
- Quick and easy installations
- InformaCast® and Syn-Apps versions available
- Indoor use



Description:

The VIP-580A IP Vandal-Resistant FlexHorn™ is designed with the same functions of the traditional FlexHorn, but incorporates tamper-resistant faceplate and resistant screw removal. The Vandal-Resistant FlexHorn is also designed with a steel mesh security baffle that prevents objects from penetrating the speaker. The horns are available as one-way or talkback. Ideal for schools, prisons, industrial or areas where speakers could be a target for vandalism.

SPECIFICATIONS

SPEAKER ELEMENT

3.5-inch (8.9cm)

Voice coil: 0.75dia (1.90cm), 45 Ohm

AUDIO OUTPUT

Rating: 108 dB @ 4ft (1.22m)

Signal/noise ratio: -70 dB

POWER REQUIREMENTS

Power over Ethernet (POE) 802.3af compatible

FREQUENCY RESPONSE

400 Hz - 10 kHz

DISPERSION

120° horizontal 90° vertical

AUDIO CODECS

G.711 u-law, others

NETWORK

10/100 Mbps Ethernet port

Manual or Dynamic Host Configuration Protocol (DHCP) IP address setup

Time and date synchronization using NTP

MOUNTING

Surface mounting on a solid surface

ENVIRONMENT

Temperature: 32 to 104 °F (0 to +40 °C)

Humidity: 0 to 85% non-precipitating

HOUSING AND FINISH

Heavy gauge steel

DIMENSIONS AND WEIGHT

10.00in H x 12.20in W x 4.0in D
(25.40cm x 30.99cm x 10.16cm)

Weight: 7.40lbs (3.40kg)

Shipping Weight: 11.00lbs (4.95kg)

2022 Rev. 1.9.6

Technical Specifications

ARCHITECTS AND ENGINEERS

The IP Vandal-Resistant FlexHorn, model VIP-580A, shall enable loudspeaker voice paging anywhere on an Ethernet network. The VIP-580A shall consists of a network connected high-efficiency horn, allowing stand alone capability when used with a SIP telephone system or can be accessed from a variety of Valcom managed VoIP products. Power shall be provided to the VIP-580A via a Power over Ethernet (PoE) switch meeting the 802.3af specification. Setup of the VIP-580A all be via the Valcom IP Solutions Setup Tool.

The VIP-580A IP Flexhorn shall be constructed of high impact ABS. The VIP-580A vandal-resistant enclosure shall be constructed with heavy gauge steel and shall be equipped with a steel mesh security

baffle and tamper-resistant faceplate screws. The VIP-580A shall be suitable for indoor installations.

The VIP-580A shall be designed with mounting holes for single-gang, double-gang or octagon outlet box or attachment to any solid surface.

Maximum dimensions shall be: 10.00in H x 12.20in W x 4.0in D (25.40cm x 30.99cm x 10.16cm). Weight shall be approximately: 7.40lbs (3.40kg).

Warranty information may be found on our website at www.valcom.com/warranty.