# AVTEO

### PLASMA & LCD CARTS



**DIMENSIONS:** 

Load Capacity: 350 lbs.

**EXTERIOR** 

Height - 32"

Width - 42"

Depth - 27"

**INTERIOR** 

Height - 17 1/2"

Depth - 14"

Rack to Glass - 1 7/8"

Rack Width - 13 7/8"

Rack Units - 10 RUs

SHIPPING BOX (Palletized)

Length - 48"

Width - 40"

Height - 51"

Ship Weight - 230 lbs





Ask about customized design and prototype capabilities

The GMP-200S is a 32" tall cart that holds a single display up to 42". Comes standard with 10RU 19" rack mount bracket in front and rear, 6 port surge protector, adjustable shelf and has an interior depth of 14". Includes universal screen mounting system and set-top camera mount (TT-1).

Please include model number of screen when ordering.

## **GMP - 200S - TT1**

SOLID STEEL CARTS

#### The most **FEATURES** on the market:

- ▶ One adjustable interior rack mounted shelf
- ▶ 6 Port surge protector
- Cable management features
- Tempered, tinted locking front glass door
- Bolted rear panel for easy access to equipment
- Standard 19" front and rear rack mount brackets,
  10RUs of space
- Standard adjustable v/c camera platform
- ▶ 32" Height for optimal face to face communication
- Standard 4" double truck ball bearing casters, two with brake
- 100% Solid steel construction

#### Choose your OPTIONS:

- Additional rack mount shelf (US-1)
- Rack mounted AmpliVox®speaker module (PSM-200)
- Heavy duty 6" caster upgrade
- Single gang Wall Plates (3 RCA, VGA+Audio and VGA+Audio+LAN)
- ▶ 6 Port rack mount surge protector (RCK-PWR)
- Custom cut Rack Shelf for Lifesize<sup>®</sup>, Polycom<sup>®</sup> and Tandberg<sup>®</sup> codecs
- Revolabs® Shelving System in various configurations for wireless microphone integration



Furniture Engineered For Today's Technology