

GA100-32T VoIP Gateway

This product can be used to convert analog telephone lines from operators and enterprise PBXs into SIP to connect to the softswitch system on the IP side, delivering a powerful, stable, reliable, and cost-effective VoIP solution for IP call centers and multi-branch offices.



Highlights

- Supports 32 FXO voice access ports and is equipped with 4 Ethernet ports
- Enables seamless call conversion between TDM and IP; supports configuration via a Web interface as well as software update and upgrade.
- Facilitates efficient management and maintenance: a quick installation wizard and Web management page are provided.
- Supports SIP/IMS protocols and VPN client functionality; its FXO ports support polarity reversal transmission. It offers strong compatibility with various softswitch platforms and excellent adaptability.
- Features a professional hardware-based echo cancellation design to ensure high-quality voice communication.

Generic

- Supports 32-channels (FXO) voice services
- Enable 32 concurrent calls
- Supports conversion between TDM and IP calls
- Supports SIP/IMS registration
- SIP Agent
- NET Settings
- Supports Simultaneous Registration of Multiple Servers (Primary and Backup)
- Centralized management
- Tone Detector
- Number Change
- Automated Gateway Configuration Deployment
- ACL extension registration and web access support ACL

Audio

- Narrowband codec : G.711a/u, G.723, G.729A/B, iLBC, AMR
- DTMF mode : In-band, Out-of-Band (RFC2833/ SIP Info)
- Acoustic Echo Canceller (AEC)

FXO Features

- Caller Detection
- Secondary Dialing
- Polarity Reversal Detection
- Tone Detection
- Outgoing Call Barring
- Incoming Call Blacklist
- FXO Disconnection Alarm

Network

- 10/100/1000 Mbps Ethernet
- IP Mode:IPv4/IPv6
- IP Configuration: Static IP / DHCP
- IP address and DNS domain name resolution
- Support VPN client
- Firewall

Protocols

- TCP
- UDP

- HTTP/HTTPS
- ARP/RARP
- DNS
- NTP
- TFTP
- TELNET
- STUN
- TR069
- SRTP
- TLS
- SIP/IMS
- SNMP

Deployment & Management

- Web Management
- Supported Languages: Chinese, English, and Russian
- Firmware Upgrades
- Tracing test Web-based Ping test/Tracert test
- Supports administrator authentication
- Monitors system and service status
- Support centralized management by a third party
- Automatic Deployment
- Syslog (Error, Warning, Info, Debug)

Physical Specifications

- FXO Ports: RJ11 x32
- Ethernet Ports: RJ45 x4
- USB Port x1: Mini USB x1
- Lightning Protection Grade: Level 4
- Reset Button x1: Press and hold for 8 seconds to restore to factory settings
- Indicator lights: PWR, RUN, ALM, FXO
- Power Consumption: <9W
- Working temperature: 0°C~45°C
- Storage Temperature: -20°C~85°C
- Working humidity: 8%~90%, No condensation
- Storage Humidity: 8%~90%, No condensation
- Qty/CTN: 5 pcs
- N.W/CTN: 13.5 kg
- G.W/CTN: 17.5 kg
- Product weight: 2.7 kg / 3.3 kg(with packaging)
- Device Dimensions: 440 x 44 x 202 mm
- Gift Box Dimensions: 538 x 250 x 87 mm
- Outer CTN Dimensions: 553 x 500 x 270 mm