

DS-KAD606-P Video/Audio Distributor

- Built-in 24 VDC Power Supply
- Six 10/100 Mbps LAN Ports with Network Cable Power
- Two 10/100 Mbps Cascading LAN Ports
- IEEE802.3, IEEE802.3u, IEEE802.3x
- Storing and Forwarding Function
- VLAN Technology
- 1,000,000+ Hours MTBF
- Wall Mounting Optional




The DS-KAD606-P Video/Audio Distributor provides network connectivity and power with eight 10/100 Mbps LAN ports. The unit features high reliability, easy installation, low maintenance, a quick exchange function, and multiple access ports. It is suitable for all digital video interconnection networks in residential areas.

Available Models: DS-KAD606-P (with power supply)

Dimensions

Specifications



DS-KAD606-P	
Network	
Interfaces	Eight 10/100 Mbps interfaces
Interface Type	RJ-45, full/half-duplex, MDI/MDI-X self-adaptive
Standard	IEEE802.3, IEEE802.3u, IEEE802.3x
Processing Type	Storing and forwarding
Flow Control	IEEE802.3x (full-duplex), back pressure (half-duplex)
Priority Queue	4
Maximum VLANs	64
VLAN ID No.	VID1 to VID4094
MAC Address List	8K
Internal Buffer	1 Mbit
General	
Power Supply	24 VDC (power adapter included)
Power Consumption	≤ 8 W
Working Temperature	14° to 131° F (-10° to 55° C)
Working Humidity	10% to 90%, non-condensing
Certifications	CE, FCC, UL 60950-1
Dimensions (L × W × H)	69.3" × 35.8" × 12.6" (176 mm × 91 mm × 32 mm)

Typical Application

