Poly OBi VVX 350 6-Line IP Phone and PoE-enabled

Sound your best

Welcome to the big leagues with this high-quality, color, six-line business IP phone that gets the job done. For high-volume call environments that demand reliability, the Poly VVX 350 desk phone won't let you down.



*Product image may differ from actual product

Conversations stay on track

Hear every nuance on the VVX 350 with Poly HD Voice technology. And reduce distracting background noise with Poly Acoustic Fence technology.

Deploy easily and quickly

IT will appreciate zero-touch provisioning and web-based management capabilities that take the headache out of telephony deployment and support.

Integrated protection 1

Your phones stay cleaner for longer with integrated Microban® antimicrobial product protection ¹ actively reducing the growth of bacteria 24/7.

Datasheet



Poly OBi VVX 350 6-Line IP Phone and PoE-enabled

Specifications



Display

Native resolution: 320 x 240
Panel technology: Color LCD
Display size (diagonal): 3.5"

Display size (diagonal, metric): 8.9 cm (3.5")

Connectivity and communications

External I/O ports:

 $2\,USB\,20\,Type-A (for media, storage applications, headset, optional Wi-Fi adapter) <math display="inline">2\,RJ-45\,(10/100/1000BASE-TX\,Mbps)$

Battery

Power features

Built-in auto sensing IEEE 802.3af Power over Ethernet (Class 0) $13\,\mathrm{W}\,\mathrm{(maximum)}^3$

User interface features

Lanauaaes:

Chinese; Danish; Dutch; English; French; German; Japanese; Korean; Norwegian; Spanish; Swedish; Finnish (Chinese) (Chinese)

Audio

Audio features:

Poly HD Voice

Poly Acoustic Clarity technology provides full duplex conversations, acoustic echo cancellation, and background noise suppression

 $Poly A coustic Fence \, technology \, eliminates \, background \, noise \, when \, using \, a \, handset \, or \, wired \, headset \, declared a constant of the contract of the contrac$

Poly Computer Audio Connector app installed on your PC (Windows only) enables selecting your phone for PC audio in/out to use the phones handset, optional headset and handsfree speakerphone with PC applications

 $Individual\ volume\ settings\ with\ visual\ feedback\ for\ each\ audio\ path$

Voice activity detection

Comfort noise generation

DTMF tone generation (RFC 2833 and in-band)

Low delay audio packet transmission

Adaptive jitter buffers

Frequency response (microphone): 150 Hz to 7 kHz

Audio codecs:

G.711 (A-law and µ-law)

G.722

G.729AB iLBC OPUS

Environmental

Certifications and compliances: AS/NZS 60950-1; Australia RCM; Brazil ANATEL; CAN/CSA C222 No. 62368+14EN 60950-1; CE Mark; CISPR22 Class B; EN 60950-1 & EN 62368+; EN55024; EN55032 Class B; EN61000-3-2; EN61000-3-3; FCC Part 15 (CFR 47) Class B; ICES-003 Class B; IEC 60950-1 & IEC 62368+1; NZ Telepermit; ROHS compliant; So. Korea KC; Saudi Arabia CITC; So. Africa ICASA; UAE TRA; UL 60950-1 and UL 62368+1; VCCI Class B; Indonesia SDPPI; Mexico NOM ANCE: Russia CU Mexico NOM ANCE: Russia CU Mexico NOM ANCERussia CUTAA

Operating humidity range: 5 to 95%

Operating Temperature Range (Celsius) / Operating Temperature Range (Fahrenheit): $0 \text{ to } 40^{\circ}\text{C} / 32 \text{ to } 104^{\circ}\text{F}$ Storage temperature range (Celsius) / Storage temperature range (Fahrenheit): $-40 \text{ to } 70^{\circ}\text{C} / -40 \text{ to } 158^{\circ}\text{F}$ Energy star certified: FNFRGY STAR* certified

Certifications

Special features:

Adjustable desk stand (2 positions) Unicode UTF-8 character support²

Applications supported

Management software:

Poly Lens

Poly Zero Touch Provisioning

Polycom Device Management Service for Service Providers (PDMS-SP) Cloud Management SDP

Display features

Digital picture frame

Security

Security management:

802.1X Authentication and EAPOL Media encryption via SRTP

Digest authentication

Encrypted configuration files

HTTPS secure provisioning

Password login

Support for signed software executables

Support for URL syntax with password

Transport Layer Security (TLS)

SRTP media encryption using AES 256 bits

Network

Supported network protocols:

10/100/1000 Base-TX across LAN and PC ports

 $Conforms \ to \ IEEE 802.3-2005 \ (Clause \ 40) \ for \ physical \ media \ attachment$ $Conforms \ to \ IEEE 802.3-2002 \ (Clause \ 28) \ for \ link \ partner \ auto-negotiation$

Manual or dynamic host configuration protocol (DHCP) network setup **VoIP features:**

24 lines (SIP registrations)

Poly OBi VVX 350 6-Line IP Phone and PoE-enabled

Specifications



Headset and handset compatibility

Headset ports:

1 Electronic Hook Switch (EHS) port for optional adapter

Headset and handset compatibility:

Compatible with commercially available TTY adapter equipment

Compliant with ADA Section 508 Subpart B 1194.23 (all)

Hearing aid compatibility to ITU-TP.370 and TIA 504A standards

Hearing aid compatible (HAC) handset for magnetic coupling to hearing aids

Telephony and call handling features Telephony and call handling features:

Anonymous call indication

Block anonymous call

Busy Lamp Field (BLF)

Call forward on busy, on no answer, unconditional

Call return

Distinctive incoming call treatment/call waiting

Do not disturb function

Shared call/bridged line appearance

Corporate directory

Call park/retrieve

Directed call pickup

Flexible line appearance (one or more line keys can be assigned for each line extension)

Up to 6 SIP registrations per phone

Integrated IVR and Auto attendant

Up to 3-way locally mixed conference call

Call waiting

Maximum sessions control

External conference bridging

Visual voicemail support

XML Application Framework for third-party business and personal applications¹

Weight and dimensions

Product Primary Color: Black

Package dimensions (imperial): 9.2 x 10.3 x 2.5 in Package dimensions (metric): 23.3 x 26.2 x 6.2 cm

Package weight (imperial): 228 lb

Package Weight (metric): 1004 g

Product number: 89B59AA

Country of origin

Country of origin: Made in China

Warranty

Poly standard one-year limited warranty

What is in the box

Desk stand/wall mount hardware

Handset with handset cord

Network (LAN) cable-CAT-5E

Setup sheet

Key Selling Points Footnotes

¹Microban antimicrobial product protection is a built-in active ingredient that enables products to resist the growth of microbes such as bacteria, mold, and mildew. Microban protection helps products stay cleaner, fresher, and last longer than products with untreated surfaces

Technical Specifications Footnotes

1 Most software-enabled features must be supported by the service provider platform. Please contact your IP PEX/softswitch vendor or service provider for a list of supported features. Optional wall mount kit can be ordered separately. 3 External universal AC/DC adapter, 5 VDC, 3 A, 15 W

